





Conjunto Cassettes 4 Vías (Inverter)

Frío Calor



-  Tensión: 220 V - 1 - 50 Hz / 380 - 3 - 50 Hz
-  Temp. de trabajo h/46° C, en modo frío y -15° C en Calor
-  Incluye filtro
-  Compresor y Motor DC

Características

	ATUN/N W24G		ATUN/N W36G		ATUN/N W60L	
Código Ansal	936100	936101	936102	936103	936104	936105
Capacidad Frío (kW)	3 / 6,8 / 8		4,5 / 9,5 / 13		5,9 / 14,6 / 16,3	
Potencia Eléctrica (kW)	2,15		2,47		5,38	
EER	3,72		3,85		3,85	
Capacidad Calor (kW)	2,8 / 7,2 / 8,8		5,0 / 10,8 / 13,7		6,8 / 16,9 / 18,7	
Potencia Eléctrica (kW)	2,24		2,80		5,60	
COP	3,21		3,86		3,02	
Alimentación (V / F / Hz)	200 - 1 - 50 Hz		200 - 1 - 50 Hz		380 - 3 - 50 Hz	
Ruido (dBA)	66	41	66	43	66	44
Línea Refrigerante	3/8" - 5/8"					
	Altura: 30 m - Longitud Máxima: 85 m					
Dimensiones (Ancho x Alto x Prof. - mm)	950x834x330	840x840x240	950x834x330	840x840x288	950x1380x330	840x840x288
Peso (Kg)	60	15	87,5	24,6	87,5	24,6

Mas información...



[Manual completo.](#)