




SISTEMA MINI VRF | UNIDADES INTERIORES



SEER/SCOP mayor a 4



Uniones sin soldaduras



Apta simultaneidad del 130%



Alimentación 220v-1-50Hz



Unidad Interior CST 4 Vía		TA-D										
		09Q4	12Q4	15Q4	18Q4	24Q4	28Q4	32Q4	36Q4	40Q4	48Q4	56Q4
Código ANSAL Unidad		979239	979240	979241	979242	979243	979244	979245	979246	979247	979248	NUEVO
Código ANSAL Frentes		979249 (TA-MBQ4-01E)										
Capacidad Frío	kW	2,8	3,6	4,5	5,6	7,1	8,0	9,0	10,0	11,2	14,0	16,0
Capacidad Calor	kW	3,2	4,0	5,0	6,3	8,0	9,0	10,0	11,1	12,5	16,0	18,0
Consumo	watt	80		88			110	140	165		176	170
Alimentación	v-f-hz.	220-1-50										
Caudal de Aire	l/s	210		250			330	370	460		580	
Contrapresion	Pa	ND										
Diametro Cañería	Pulg	1/4 - 1/2				3/8 - 5/8						
Dimensiones U.Interior	An/ Al/ Pr (mm)	840x230x840						840x300x840				950x 300x 950
Dimensiones Panel	An/ Al/ Pr (mm)	950x70x950										1050x 55x 1050
Peso U.Interior/ Panel	kg	21,5 /5,8	23,7/5,8				28,7/5,8		30,9/5,8		35,3 /7,4	
Procedencia		China										

MAS INFORMACION



Tadiran Series Mini F-VRF