







SISTEMA MINI VRF | UNIDADES INTERIORES

-  SEER/SCOP mayor a 4
-  Uniones sin soldaduras
-  Apta simultaneidad del 130%
-  Alimentación 220v-1-50Hz



Unidad Interior CST 1 Vía		TA-D						
		06Q1	07Q1	09Q1	12Q1	15Q1	18Q1	24Q1
Código ANSAL Unidad		979220	979221	979222	979223	979224	979225	979226
Código ANSAL Frontes		979227 (TA-MBQ1-02D)				979228 (TA-MBQ1-01D)		
Capacidad Frio	kW	1,8	2,0	2,6	3,5	4,4	5,3	7,0
Capacidad Calor	kW	2,0	2,3	2,9	3,8	4,9	6,1	7,8
Consumo	watt	41				48		
Alimentación	v-f-hz.	220 -1 - 50						
Caudal de aire	l/s	145	145	159	159	193	220	260
Contrapresion	Pa	ND						
Díametro Cañería	Pulg	1/4 - 1/2					3/8 - 5/8	
Dimensiones U.Interior	An/Al/Pr (mm)	1054x153x425				1275x189x450		
Dimensiones Panel	An/Al/Pr (mm)	1180x25x465				1350x25x505		
Peso U.Interior/Panel	kg	12,5/3,5		13/3,5		18,5/4	18,8/4	19,5/4
Procedencia		China						

MAS INFORMACION



Tadiran Series Mini F-VRF