







## SISTEMA MINI VRF | UNIDADES INTERIORES

-  SEER/SCOP mayor a 4
-  Uniones sin soldaduras
-  Apta simultaneidad del 130%
-  Alimentación 220v-1-50Hz



Baja Silueta Media Presión		TA-D										
		07T2	09T2	12T2	15T2	18T2	24T2	28T2	32T2	40T2	48T2	56T2
Código ANSAL Unidad		979260	979261	979262	979263	979264	979265	979266	979267	979268	979269	979270
Capacidad Frío	kW	2,2	2,8	3,6	4,5	5,6	7,1	8,0	9,0	11,2	14,0	16,0
Capacidad Calor	kW	2,6	3,2	4,0	5,0	6,3	8,0	9,0	10,0	12,5	15,5	17,0
Consumo	watt	57		98	103	140	198	200	313	274	940	
Alimentación	v-f-hz.	220-1-50										
Caudal de Aire	l/s	155		170	220	275	375	500	530	1000		
Contrapresión	Pa	30					45	48	100	195		
Diametro Cañería	Pulg	1/4 - 1/2						3/8 - 5/8				
Dimensiones U.Interior	An/ Al/ Pr (mm)	778x210x500			997x210x500		1218x 210x 500	1230x270x775			1290x 300x 865	1322x 423x 691
Peso U.Interior	kg	18,5			22,5	28	36			46,5	67	
Procedencia		China										

## MAS INFORMACION



### Tadiran Series Mini F-VRF