



## SISTEMA VRF HP | UNIDADES EXTERIORES

- Sistemas hasta 96 HP modulable
- Modulo máximo 26 HP
- Alimentación 380V-3-50Hz



Unidad Exterior HP LG		ARUN180LTE5	ARUN200LTE5	ARUN220LTE5	ARUN240LTE5	ARUN260LTE5
Código ANSAL Unidad Interior		937104	937105	937106	937107	937108
Capacidad Frío	kW	50,4	56,0	61,6	67,2	72,8
Consumo Frío	kW	10,0	12,3	14,8	16,8	19,4
EER		11,0	4,5	4,2	4,0	3,8
Capacidad Calor	kW	56,7	63,0	69,3	74,3	78,0
Consumo Calor	kW	12,1	15,5	17,5	18,9	19,5
COP		4,7	4,1	4,0	3,9	4,0
Alimentación	v-f-hz.	380-3-50 Hz				
Refrigerante	Tipo/Kg	R410A/13	R410A/14		R410A/16	
Diametro Cañería	Pulg	5/8 - 1 1/8			3/4 - 1 3/8	
Sum. Longitud/ Altura máxima	m	1000/110				
Dimensiones U.Exterior	An/AI/Pr (mm)	1240x1690x760				
Peso U.Exterior	kg	261	281	285	287	287
Rango de Trabajo	Frío/Calor	-15°C / 45°C				
Nº Máximo de UI	Un	29	32	35	39	42
Procedencia		Corea				

### MÁS INFORMACION



**Datos de producto (ingeniería)**