



Temperatura Ambiente: 32 °C

Temperatura de Evaporación

LBP	-23,3 °C
MBP-CBP	-6,7 °C
HBP- A/C	7,2 °C

Fluido refrigerante	Ref. Com. HP	Modelo	Capacidad Frigorífica - MBP/HBP					Dimensionais Unidade (mm)		
			-15 °C	-5 °C	0 °C	7,2 °C	15 °C	A	B	C
			Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h			
R-22	1.1/3	CAJ9513TMHR	1.376	2.032	2.393	2.921	3.546	340	430	490
	1.1/2	CAJ4517EHR	1.700	2.517	2.999	3.759	4.681	445	510	607
	2.0	FHS4524FHR	2.327	3.569	4.241	5.362	6.646	445	510	607
	2.1/2	FHS4531FHR	3.066	4.711	5.624	7.028	8.662	540	512	607
	3.0	TFH4540FHR	4.128	6.568	7.974	9.993	12.451	458	992	894
	3.1/2	TAG4546THR	4.502	7.036	8.648	11.290	14.503	562	1072	590
	4.0	TAG4553THR	5.405	8.601	10.442	13.085	16.304	565	974	560
	5.0	TAG4561THR	6.219	9.896	12.014	15.056	18.759	565	1072	590
	5.1/2	TAG4568THR	6.597	10.715	12.822	16.281	20.103	561	1072	590
	7.0	TAGD4590THR	8.508	13.102	15.641	19.596	24.232	868	1417	720
	8.0	TAGD4610THR	9.661	15.022	17.949	22.476	27.725	868	1417	720
	10.0	TAGD4612THR	12.029	18.493	22.313	27.750	34.412	868	1417	720
	11.0	TAGD4614THR	12.513	19.557	23.584	30.014	37.680	868	1417	720
12.0	TAGD4615THR	14.678	22.003	26.210	32.953	41.015	868	1417	720	
R404A	1.1/3	CAJ9513ZMHR	1.600	2.234	2.563	3.036	3.359	340	430	490
	1.1/2	CAJ4517ZHR	1.960	2.823	3.256	3.865	4.502	445	510	607
	2.0	FH4524ZHR	2.694	3.887	4.506	5.423	6.445	445	510	607
	2.1/2	FHS4531ZHR	3.814	5.551	6.439	7.746	9.185	540	512	607
	3.0	TFH4540ZHR	4.608	6.548	7.563	9.070	10.771	458	992	894
	3.1/2	TAG4546ZHR	5.298	8.040	9.535	11.834	14.519	562	1072	590
	4.0	TAG4553ZHR	5.650	8.522	10.059	12.391	15.074	565	974	560
	5.0	TAG4561ZHR	6.453	9.845	11.666	14.436	17.633	565	1072	590
	5.1/2	TAG4568ZHR	7.350	11.460	13.477	16.340	19.383	561	1072	590
	7.0	TAGD4590ZHR	10.064	15.010	17.562	21.338	25.540	868	1417	720
	8.0	TAGD4610ZHR	10.932	16.544	19.554	24.146	29.404	868	1417	720
	10.0	TAGD4612ZHR	13.471	19.538	22.644	27.201	32.251	868	1417	720
	11.0	TAGD4614ZHR	15.777	23.031	26.460	31.129	35.804	868	1417	720
12.0	TAGD4615ZHR	17.791	24.010	27.769	33.992	41.635	868	1417	720	

Fluido refrigerante	Ref. Com. HP	Modelo	Capacidad Frigorífica - LBP					Dimensionais Unidade (mm)		
			-40 °C	-30 °C	-23,3 °C	-20 °C	-10 °C	A	B	C
			Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h			
R404A	1.1/2	CAJ2464ZBR	633	1.110	1.493	1.697	2.367	320	440	480
	2.0	FH2480ZBR	863	1.645	2.242	2.539	3.424	420	515	607
	3.0	FH2511ZBR	1.004	2.127	2.917	3.327	4.506	450	510	630
	4.0	TAG2516ZBR	1.651	3.179	4.355	4.979	7.024	456	992	894
	5.0	TAG2522ZBR	2.173	4.013	5.415	6.156	8.569	565	1072	590
	8.0	TAGD2532ZBR	2.991	5.998	8.421	9.735	14.202	670	1417	738
	10.0	TAGD2544ZBR	4.075	7.633	10.349	11.785	16.529	670	1417	738

Toda la información contenida en este instructivo esta sujeta a cambios sin previo aviso.