



SISTEMA MINI VRF | UNIDADES EXTERIORES



SEER/SCOP mayor a 4



Uniones sin soldaduras



Monocaño



Apta simultaneidad del 130%



Alimentación 220v-1-50Hz



Mas informacion:



Certificado:



Unidad Exterior		TA-V					
		28WDH	36WDH	42WDH	48WDH	56WDH	60WDH
Código ANSAL		979202	979204	979206	979208	979210	979212
Capacidad Frío	kW	8,0	10,0	12,0	14,0	16,0	18,0
Consumo Frío	kW	2,1	2,7	3,3	3,9	4,9	6,1
EER		3,8	3,7	3,6	3,6	3,3	3,0
Capacidad Calor	kW	9,0	12,0	14,0	16,0	18,0	19,5
Consumo Calor	kW	2,4	3,2	3,6	3,9	4,8	5,6
COP		3,8	3,8	3,9	4,1	3,8	3,5
Alimentación	v-f-hz.	220-1-50					
Refrigerante	Tipo/Kg	R410a/1,7	R410a/2,3	R410a/2,4	R410a/3,1	R410a/3,6	R410a/4,6
Diametro Cañería	Pulg	3/8 - 5/8				3/8 - 3/4	
Sum. Longitud/ Altura máxima	m	50/10	65/20		100/30		130/30
Dimensiones U.Exterior	An/Al/Pr (mm)	910x712x426		950x840x440			1040x865x 523
Peso U.Exterior	kg	49	60	63	75	78	91
Rango de Trabajo	Frío/Calor	-5°C - 55°C / -15 °C - 27°C					
Procedencia		China					