

VRM-2S

VRM-2SV

Smart Digital Manifold Gauge

NEW



Gancho



Display digital retroiluminado



Resistencia al impacto



VTS-1S Lado de baja

VMT-2S Lado de alta



Pinzas de temperatura
conexión alta y baja

Inteligente y preciso

Inteligente e inalámbrico

- Funciona con la app Hi VALUE
- Conexiones Bluetooth con pinzas de temperatura y manómetro de micrones (se venden por separado)

Modos de operación múltiple

- Modo manifol con visualización SH/SC
- Modo prueba de presión
- Modo evacuación

Digital y preciso

- Precisión clase 0.4 con pantalla digital
- Precisión visible de un vistazo

Cuerpo de aluminio con válvula de 1/4 de vuelta

- Confiable, eficiente y duradero
- Mejor experiencia de trabajo

Gancho plegable

- Diseño de gancho oculto
- Fácil de transportar

Resistente a impactos

- Diseño resistente a impactos
- Cubierta de goma duradera

Modelo	VRM-2S	VRM-2SV
Tipo de refrigerante	R-11, R-12, R-13, R-22, R-23, R-32, R-113, R-114, R-115, R-116, R-123, R-124, R-125, R134A, R-236fa, R-245fa, R-290, R401A, R-401B, R-402A, R-402B, R-403B, R-404A, R-406A, R-407A, R-407B, R-407C, R-408A, R-409A, R-410A, R-413A, R-414A, R-414B, R-416A, R-417A, R-417C, R-420A, R-421A, R-421B, R-422A, R-422B, R-422C, R-422D, R-424A, R-427A, R-428A, R434A, R-437A, R-438A, R-448A, R-449A, R-450A, R-452A, R-452B, R-453A, R-454B, R-458A, R-500, R-501, R-502, R-503, R507A, R-508B, R-513A, R-600, R-600a, R-601, R-601a, R-744*, R-1233zd, R-1234yf, R-1234ze Firmware can be updated at VALUE website or with Hi VALUE App *Maximum pressure: 725 Psi (5000 kPa)	
Rango de presión	-30 inHg to 725 psi	
Rango Bluetooth	80 m line of sight	
Batería	Rechargeable Li-ion Battery	
Accesorios	Bluetooth Temperature Clamps VMT-1S (Low Side), VMT-2S (High Side), Charging Cable, Carry Case	VMV1S Micron Gauge in addition to the VRM-2S Kit