

R410A

R410A AIR-CONDITIONER COMPRESSOR

Series	Typical Model	Displ. (cm ³ /rev)	Cooling Capacity (W) (Btu/h)		Power (W)	COP (W/W)	Capacitor (µ F/V)	Compressor Height (mm)	Discharge Pipe ID (mm)	Sucition Pipe ID (mm)	Remark
--------	---------------	----------------------------------	-----------------------------------	--	--------------	--------------	----------------------	---------------------------	---------------------------	--------------------------	--------

R410A

1φ- 50Hz- 220/240V

Test Condition:ASH

SK	ASK40V11UAZ	4.0	930	3173	365	2.55	15/370	230	8.1	9.8	
SN	ASN68V1UZZ1	6.8	1695	5783	585	2.90	20/370	250	8.1	9.8	
	ASN76V1UDZ1	7.6	1890	6449	630	3.00	25/370	250	8.1	9.8	
	ASN82V1UDZ	8.2	2035	6943	690	2.95	25/370	250	8.1	9.8	
	ASN86V1UDZ	8.6	2140	7302	725	2.95	25/370	250	8.1	9.8	
SM	ASM99V2UDZ	9.8	2395	8172	788	3.04	25/370	292	8.1	9.8	
M2	PA170M2C-4ET2	17.1	4190	14296	1385	3.03	35/400	300	8.1	12.9	
	PA185M2C-4FT2	18.5	4495	15337	1500	3.00	35/400	300	8.1	12.9	
	PA200M2A-4ET2	20.0	5000	17060	1695	2.95	40/370	314	9.8	12.9	
	PA215M2AS-4KU	21.5	5355	18271	1845	2.90	50/400	314	9.8	12.9	
	PA225M2CS-4KU2	22.4	5500	18766	1835	3.00	50/370	340	8.1	12.9	
	PA240M2CS-4KU1	23.9	5840	19926	1980	2.95	50/370	340	8.1	12.9	
SF	ASF205V1UEUB	20.5	5160	17606	1655	3.12	45/400	314	8.1	12.9	
	ASF205V1UKTB3	20.5	5085	17350	1620	3.14	55/400	314	9.8	12.9	
	ASF205V2UKTH3	20.5	5205	17759	1635	3.18	55/400	314	8.1	12.9	▲
	ASF210V2UFTB3	21.0	5310	18118	1670	3.18	55/400	314	8.1	12.9	▲
SG	ASG230V1UKT	22.9	5785	19738	1830	3.16	45/400	310	9.8	12.9	
	ASG270V1UMT	27.1	6880	23475	2175	3.16	45/400	310	9.8	16.2	
	ASG280V1UMP	27.9	7065	24106	2340	3.02	60/400	310	9.8	16.2	
SQ	ASQ330V1UM T	33.1	8330	28422	2740	3.04	70/400	380	9.8	16.2	
TG	ATG330V1UM P	32.7	8230	28081	2815	2.92	65/400	380	9.8	16.2	
TQ	ATQ375V1UMU	37.7	9615	32806	3255	3.05	75/400	405	9.8	16.2	
	ATQ390V1UMT	38.9	9825	33523	3190	3.08	70/400	405	9.8	16.2	