



Compresores Hermeticos Media Temperatura R404



Screw thread connection type Refrigerant: R404a/R407

Compressors models	Horse Power(H.P.)				REFRIGERATION CAPACITY AT 50Hz rated @ 54.5°C/130°F Cond.Temp(Watts)						
	Displacement(cm ³)				Evaporating Temperature						
	Weight(kg)				Power source						
	Oil charge(cm ³)				-25°C -12°F	-15°C +5°F	-10°C +14°F	0°C +32°F	+7.2°C +45°F	+15°C +59°F	
					220V/3PH/60Hz	380V/3PH/50Hz	380V/3PH/60Hz	460V/3PH/60Hz			
QR3-44	2	44	31	1500	220V/3PH/60Hz 380V/3PH/50Hz 380V/3PH/60Hz 460V/3PH/60Hz	1379*	1850	2580	4370	5977	8110
QR3-52	2.5	52	31			1508*	2260	3240	5400	7146	9320
QR3-58	3	58.2	33			1635*	2390	3310	5720	7967	10240
QR3-62	3	62.7	33			1998*	2970	3960	6420	8613	11540
QR3-74	3.5	74.2	33			3078*	2805	4296	7276	9814	13056
QR3-90	4	90.2	46	2000		1510	3388	4425	7956	11300	15719
QR3-112	5	112.5	46			3965	4360	5890	10450	14780	20230
QR3-124	6	124.4	48			5146	5320	7080	11970	16650	22760
QR3-134	7	134.8	48			5453	5780	7710	13120	18230	24806

Condensing Temp Range ≤65°C

Compressor Internal Protectors: Internal Motor Protector and Pressure Relief Valve

To obtain refrigeration capacity at 60Hz, multiply its values at 50Hz by 1.2

*Condensing Temp:45°C