



Compresores Hermeticos Baja Temperatura R404



Screw thread connection type

Refrigerant: R404a/R407

Compressors models	Horse Power(H.P.)				REFRIGERATION CAPACITY AT 50Hz rated @54.5°C/130°F Cond.Temp(Watts)							
	Displacement(cm ³)				Evaporating Temperature							
	Weight(kg)				Power source							
	Oil charge(cm ³)				-40°C -40°F	-35°C -31°F	-30°C -22°F	-23.3°C -9.9°F	-20°C -4°F	-10°C +14°F	0°C +32°F	
					220-240V/1PH/50Hz	208-230V/1PH/60Hz	220V/3PH/60Hz	380V/3PH/50Hz	380V/3PH/60Hz	460V/3PH/60Hz		
QL52	2.5	52	33	1500	475*	836	1410	2068	3037	5050	5300	
QL62	3	62.7	35		1136*	1286	1993	2617	3660	6130	6300	
QL3-52	2.5	52	31		475*	836	1410	2068	3037	5050	5300	
QL3-74	3.5	74.2	32		1404*	1521	2358	3051	4333	7265	7330	
QL3-112	5	112.5	46	2000	1646*	2035	3164	4365	6231	10550	10600	
QL3-134	7	134.8	46		2354*	2782	4177	5428	7892	12120	12630	

Condensing Temp Range ≤65°C

Compressor Internal Protectors: Internal Motor Protector and Pressure Relief Valve

To obtain refrigeration capacity at 60Hz, multiply its values at 50Hz by 1.2

*Condensing Temp:50°C