




**Visores de Líquido BlueStar**

**Parámetros:**

Modelo	Conexión (pulg)	Conexión	A	B	C	D	E	F	L	S	
8200-04	1/4"	ODF	8.5	14.5	26.5	6.5	7	27	100	14	N/A
8201-04		SAE				N/A	N/A	14	64		7/16-20UNF
8202-04		FM				9.5	15	12	59		N/A
8200-06	3/8"	ODF	8.5	14.5		10.1	8	36	118	19	N/A
8201-06		SAE				N/A	N/A	17	70		5/8-18UNF
8202-06		FM				12	17	15	65		N/A
8200-08	1/2"	ODF	11.5	16.5	12.8	10	46	144	22	N/A	
8201-08		SAE			N/A	N/A	19	78		3/4-16UNF	
8202-08		FM			13.5	18	18	70		N/A	
8200-10	5/8"	ODF	13	18	16.1	14	49	150	24	N/A	
8201-10		SAE			N/A	N/A	20	78		7/8-14UNF	
8200-12	3/4"	ODF	14	20	19.1	16	51	166	27	N/A	
8201-12		SAE			N/A	N/A	23	94		1-1/16-14UNF	
8200-14	7/8"	ODF	15.5	21.5	22.3	17	54	172	34	N/A	
8200-18	1-1/8"	ODF	18.5	23.5	28.7	18	69	212	34	N/A	

**Contenido de humedad vs cambio de color:**

INDICACIÓN (PPM DE AGUA)	SECO (VERDE)	PRECAUCION (VERDE CLARO)	HUMEDO (AMARILLO)	SECO (VERDE)	PRECAUCION (VERDE CLARO)	HUMEDO (AMARILLO)
TEMPERATURA DEL AGUA °C	25°C			43°C		
R22/R502	< 30	30-120	> 120	< 50	50-200	> 200
HFC-134a	< 30	30-100	> 100	< 45	45-100	> 170
R404a	< 20	20-70	> 70	< 25	25-100	> 100
R407C	< 30	30-140	> 140	< 60	60-225	> 225
R507	< 15	15-60	> 60	< 30	30-110	> 110
R401A	< 66	66-266	> 266	< 135	135-540	> 540
R410A	< 60	60-280	> 280	< 75	75-420	> 420