



(related parameters)	(compressor type)	MQ-GQR12TG	(test number)	20181024		
	(prototype number)	02760#	(test basis)	GB/T9098-2008	(testing personnel)	2
	(producing area)		(type of compressor)		(speed (frequency))	
	(capacitance)	50	(Cryogen)	R134a	(rated current)	
	(rated capacity)		(rated power)		(rated COP)	
(test conditions)	(project)	(evaporation temperature)	(condensing temperature)	(suction temperature)	(supercooling temperature)	ambient temperature)
	(parameters)	7,2	54,4	35	46,1	35
(project)	(unit)	(Record one)	(Record two)	(Record three)	(Record four)	(average)
(supply voltage)	V	220,3	220,3	220,3	220,3	220,3
(supply current)	A	3,02	3,02	3,02	3,02	3,02
(supply frequency)	Hz	50	50	50	50	50
(input power)	W	544,04	544,08	543,95	544,24	544,08
(power factor)	/	0,82	0,82	0,82	0,82	0,82
(evaporation temperature)	°C	7,14	7,16	7,15	7,16	7,15
(condensation temperature)	°C	54,45	54,43	54,43	54,46	54,44
(supercooling temperature)	°C	46,11	46,1	46,09	46,11	46,1
(suction temperature)	°C	35,22	35,24	35,26	35,26	35,25
(ambient temperature)	°C	35,01	35	35,01	35,03	35,01
(exhaust temperature)	°C	93,18	93,19	93,16	93,18	93,18
(condenser outlet Temp)	°C	28,87	28,64	28,47	28,26	28,56
(calorimeter outlet Temp)	°C	35,18	35,21	35,21	35,21	35,2
(shell temperature)	°C	62,69	62,73	62,65	62,71	62,7
(vessel room temperature)	°C	28,19	28,67	28,86	29,18	28,73
(suction pressure)	MPa	0,3764	0,3767	0,3765	0,3766	0,3766
(exhaust pressure)	MPa	1,4715	1,4709	1,471	1,4719	1,4713
(calorimeter-inlet Press)	MPa	1,4777	1,4772	1,4774	1,4785	1,4777
(pressure in the calorimeter)	MPa	0,4866	0,4866	0,4866	0,4866	0,4866
(calorimeter-Outlet Press)	MPa	0,3793	0,3796	0,3795	0,3796	0,3795
(calorimeter heating power)	W	1305,5	1304,57	1304,47	1303,5	1304,51
(cooling capacity)	W	1306,6	1304,62	1304,78	1303,49	1304,87
COP	/	2,402	2,398	2,399	2,395	2,399
(compressor speed)	r/min	0	0	0	0	0

(cold-main winding)	Ω	7,06	(cold- secondary winding)	20,79
(cold-state temperature)	°C	22,95	(winding material)	
(hot-main winding)	Ω	8,56	(hot- secondary winding)	26,17
(main winding resistance temperature)	°C	77,61	(secondary winding resistance temperature)	89,59

Toda la información contenida en este instructivo está sujeta a cambios sin previo aviso.

