Te: (5411) 4958 2884 Fax: (5411) 4958 2886

Otamendi 530 (C1405BRH) Buenos Aires - Argentina ansal@ansal.com.ar http://www.ansal.com.ar



Código: 920639 Garrafa 10,9Kg-R404--"BlueStar"------



Common Data

Description

A colourless, non-flammable gas at atmospheric pressure with a slight ethereal odour. Supplied in low pressure cylinders.

Physical Properties

Refrigerant Components	R-125/143a/134a
	(44/52/4)
Bubble Point	
°C@101.3kPa	-46.2
°F@14.7psia	-51.2
Critical Temperature	
°C	72.1
°F	161.8
Purity	99.8
% by weight(min)	
Water Content	10
ppm by weight(max)	
Acidity	1.0
ppm by weight(max) (as HO	CI)
Non Condensable Gasses	1.5
Content measured on vapou	ur phase
% by volume(max)	
Residues at High Boiling Po	oint 0.01
% by volume(max)	
Chloride	pass
No visible turbidity	

Classifica

H.S.Code	38247900
UN Number	3337
Class	2.2

Uses and Features

- Commerial and medium temperature refrigeration applications.
- A replacement for CFC-502.

Material Compatibility

Most common materials are suitable for use under normal conditions in a dry system, At high temperatures, use stainless steel or Inconel to resist corrosive breakdown products. Avoid using alloys with more than 2% magnesium(i.e.some aluminium alloys) especially when moisture is present. May react violently with sodium, potassium, barium and other alkali or alkaline earth metals. Flexible hoses or gaskets should not contain natural rubber as rapid withdrawals of gas/liquid can extract compounding ingredients and it also suffers from excesive swelling.

Package:

• Non-refillable cylinder of 10.9Kgs

Oil Com

• POE

